

an alarm situation is imposed. This evaluation can be carried out by a comparison of successive images, a comparison of a current image with a stored image or else by a computation algorithm which, for example, detects a movement in the running coding algorithm. If the calculated motion vector exceeds a certain threshold value,
5 the alarm is triggered.

The triggering of the alarm causes the connection to be set up to a supervisory or surveillance center to which a preconstructed alarm text or an alarm message can be transmitted. The alarm-triggering image is additionally transmitted. This enables the surveillance center to check whether the alarm was triggered by an
10 intruder, or whether a false alarm is involved; for example, caused by a cat.

It is conceivable to use a wireless video telephone system instead of the video telephone apparatus. Such a system operates, for example, according to the DECT standard (or the Japanese PHS standard), in which a video
mobile part is wirelessly connected to a base station.

When a video telephone terminal or a video telephone system is used for a surveillance method, it is possible for the intruder to destroy the alarm-signaling apparatus before a communications link to the central security station has been set
15 up, or at least to disconnect it from the network.

The present invention is, therefore, directed toward specifying a more
20 secure surveillance method.

SUMMARY OF THE INVENTION

The present invention is based on the idea of immediately transmitting the alarm-triggering image sequence or the alarm-triggering image from the mobile apparatus to the base station. This transmission takes place right away, with the
25 result that it is practically impossible for an intruder to destroy the mobile apparatus before the image transmission. The base station then has enough time to set up the connection to the central surveillance station and to transmit the transmitted, buffer-stored image there.

Additional features and advantages of the present invention are described in,
30 and will be apparent from, the following Detailed Description of the Invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is described below using an exemplary embodiment.

By way of example, a cordless telephone system according to the DECT standard is assumed to be known. Such systems and similar systems are described, for example, in Funkschau, Issue 13, Year 97 in the article "Comparison of DECT and PHS". Building on this, the mobile part can be provided with a camera, so that a corresponding video telephone system is present for carrying out wireless video telephony. The base station of the telephone system can be connected to a wireless or corded, analog or digital communications network.

In order to set up a communications link to the communications network, a call number is input on the mobile part, for example. Once the connection has been set up, from the base station, it is possible to carry out the voice and/or image communication to a remote subscriber. Data stored in the mobile part only can be transmitted after the setup of the communications link from the mobile part via the base station to the communications network.

The present invention is based on the immediate transmission of the alarm and of the alarm-triggering image from the mobile part to the base station.

Such a video telephone system is used for a surveillance method; for example, to combat break-ins. It is of secondary importance to the present invention whether the alarm is triggered in the video mobile part or in the base station itself. In one case, the mobile part is continuously connected to the base station. In this case, the recorded images are immediately transmitted to the base station, where an image change or a movement is detected. In another case, this detection is carried out in the mobile part and, if an alarm is imposed, the alarm-triggering image is immediately transmitted to the base station. In both cases, the image or the image sequence is present in the base station before the central surveillance station is dialed from the base station.

If the mobile part is destroyed by an intruder, for example, the transmission of the associated image can no longer be prevented.

In one embodiment of the present invention, the camera of the video mobile part has image recording sensors for the infrared range.